

IGBT MODULE (F series)

■ Features

- Low Saturation Voltage
- Voltage Drive
- Variety of Power Capacity Series

■ Applications

- Inverter for Motor Drive
- AC and DC Servo Drive Amplifier
- Uninterruptible Power Supply
- Industrial Machines, such as Welding Machines

■ Maximum Ratings and Characteristics

● Absolute Maximum Ratings

Items		Symbols	Ratings	Units
Collector-Emitter Voltage		V_{CES}	1200	V
Gate-Emitter Voltage		V_{GES}	± 20	V
Collector Current	Continuous	I_C	200	A
	1ms	I_C pulse	400	
	Continuous	$-I_C$	200	
	1ms	$-I_C$ pulse	400	
Max. Power Dissipation		P_C	1440	W
Operating Temperature		T_j	+150	$^{\circ}\text{C}$
Storage Temperature		T_{stg}	-40 to +125	$^{\circ}\text{C}$
Net. Weight			415	g
Isolation Voltage	AC. 1min.	V_{isol}	2500	V
Screw Torque		Mounting *1	3.5 {35}	N · m {kg · cm}
		Terminals *2	4.5 {45}	
		Terminals *3	1.7 {17}	


● Electrical Characteristics (Tc=25°C)

Items	Symbols	Test Conditions	Min.	Typ.	Max.	Units
Zero Gate Voltage Collector Current	I _{CEs}	V _{GE} =0V V _{CE} =1200V T _J =25°C			4.0	mA
		V _{GE} =0V V _{CE} =1200V T _J =125°C			—	mA
Gate-Emitter Leakage Current	I _{GES}	V _{CE} =0V V _{GE} =±20V			400	nA
Gate-Emitter Threshold Voltage	V _{GE(th)}	V _{CE} =20V I _C =200mA	3.0		6.0	V
Collector-Emitter Saturation Voltage	V _{CE(sat)}	V _{GE} =15V I _C =200A			2.5	V
Input Capacitance	C _{ies}	V _{GE} =0V		36000		pF
Output Capacitance	C _{oss}	V _{CE} =10V		—		
Reverse Transfer Capacitance	C _{res}	f=1MHz		—		
Turn-on Time	t _{on}	V _{CC} =600V I _C =200A	Resistive load		0.8	μs
	t _r	V _{GE} =±15V			0.6	
Turn-off Time	t _{off}	R _G =4.7Ω	Inductive load		1.5	
	t _f				1.0	
Diode Forward On-Voltage	V _F	I _F =200A, V _{GE} =0V			2.5	V
Reverse Recovery Time	t _{rr}	I _F =200A, -di/dt=600A/μs V _{GE} =-10V			350	ns


● Thermal Characteristics

Items	Symbols	Test Conditions	Min.	Typ.	Max.	Units
Thermal Resistance	R _{th(j-c)}	IGBT			0.087	°C/W
	R _{th(j-c)}	Diode			0.167	
	R _{th(c-f)}	With Thermal compound		0.0125		


■ Outline Drawings




■ Equivalent Circuit Schematic




- *1 Recommendable Value 2.5 to 3.5 N•m
{ 25 to 35 kg•cm } (M5)
- *2 Recommendable Value 3.5 to 4.5 N•m
{ 35 to 45 kg•cm } (M6)
- *3 Recommendable Value 1.3 to 1.7 N•m
{ 13 to 17 kg•cm } (M4)




Collector Current vs. Collector-Emitter Voltage




Collector Current vs. Collector-Emitter Voltage




Collector-Emitter Voltage vs. Gate-Emitter Voltage



Switching Time



Switching Time



Switching Time-Gate Resistance

