



Target Specification of 1MBI300SA-120

1. Outline Drawing (Unit : mm)



2. Equivalent circuit



DATE

NAME

APPROVED

Fuji Electric Co., Ltd.

DRAWN: Feb - 11 - 99 N. Arakawa

CHECKED: Feb - 11 - 99 S. Miyatake

J. Hiyasaka

DWG. NO.

MT5F 9778

1/5

REVISIONS

3. Absolute Maximum Ratings (at $T_c = 25^\circ\text{C}$ unless otherwise specified)

Items	Symbols	Conditions		Maximum Ratings	Units
Collector-Emitter voltage	V _{CES}			1200	V
Gate-Emitter voltage	V _{GES}			± 20	V
Collector current	I _c	Continuous	T _c =25℃	400	A
			T _c =80℃	300	
	I _c pulse	1ms	T _c =25℃	800	
			T _c =80℃	600	
	-I _c			300	
	-I _c pulse	1ms		600	
Collector Power Dissipation	P _c	1 device		1900	W
Junction temperature	T _j			150	℃
Storage temperature	T _{stg}			-40~ +125	℃
Isolation voltage ^(*)	V _{iso}	AC : 1min.		2500	V
Screw Torque	Mounting ^{(*)2}			3. 5	N · m
	Terminals ^{(*)3}			4. 5	
	Terminals ^{(*)4}			1. 7	

(*) All terminals should be connected together when isolation test will be done.

(*) Recommendable Value : 2.5 ~ 3.5 N · m (M5) or (M6)

(*) Recommendable Value : 3.5 ~ 4.5 N · m (M6)

(*) Recommendable Value : 1.3 ~ 1.7 N · m (M4)

4. Electrical characteristics (at $T_j = 25^\circ\text{C}$ unless otherwise specified)

Items	Symbols	Conditions	Characteristics			Units
			min.	typ.	Max.	
Zero gate voltage Collector current	I _{CES}	V _{GE} = 0 V, V _{CE} = 1200 V			4.0	mA
Gate-Emitter leakage current	I _{GES}	V _{CE} = 0 V, V _{GE} = ± 20 V			0.8	μA
Gate-Emitter threshold voltage	V _{GE(th)}	V _{CE} = 20 V, I _c = 300 mA	5.5	7.2	8.5	V
Collector-Emitter saturation voltage	V _{CE(sat)}	V _{GE} = 15 V, T _j = 25°C		2.3	2.6	V
		I _c = 300 A, T _j = 125°C		2.8		
Input capacitance	C _{ies}	V _{GE} = 0 V		36000		pF
Output capacitance	C _{oes}	V _{CE} = 10 V		7500		
Reverse transfer capacitance	C _{res}	f = 1 MHz		6600		
Turn-on time	t _{on}	V _{cc} = 600 V			1.2	μs
	t _r	I _c = 300 A			0.6	
	t _{r(i)}	V _{GE} = ± 15 V		0.1		
Turn-off time	t _{off}	RG = 2.7 Ω			1.0	
	t _f			0.08	0.3	
Forward on voltage	V _F	IF = 300 A, T _j = 25°C		2.5	3.3	V
		T _j = 125°C		2.1		
Reverse recovery time	t _{rr}	IF = 300 A			0.35	μs

5. Thermal resistance characteristics







Items	Symbols	Conditions	Characteristics			Units
			min.	typ.	Max.	
Thermal resistance (1 device)	R _{th(j-c)}	IGBT			0.066	°C/W
		FWD			0.220	
Contact Thermal resistance	R _{th(c-f)}	with Thermal Compound (*)		0.0125		

※ This is the value which is defined mounting on the additional cooling fin with thermal compound.

Note :


- This specification is only for technical considerations, and not for contract.
- This specification is subject to be changed without notices.

This material and the information herein is the property of Fuji Electric Co Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.




This material and the information herein is the property of Fuji Electric Co Ltd. They shall be neither reproduced, copied, lent, or disclosed in any way whatsoever for the use of any third party nor used for the manufacturing purposes without the express written consent of Fuji Electric Co., Ltd.


Switching time vs. Collector current (typ.)
 $V_{CC}=600V$, $V_{GE}=\pm 15V$, $R_g=2.7\Omega$, $T_j=25^\circ C$




Switching time vs. Collector current (typ.)
 $V_{CC}=600V$, $V_{GE}=\pm 15V$, $R_g=2.7\Omega$, $T_j=125^\circ C$




Switching time vs. Gate resistance (typ.)
 $V_{CC}=600V$, $I_c=300A$, $V_{GE}=\pm 15V$, $T_j=25^\circ C$




Switching loss vs. Collector current (typ.)
 $V_{CC}=600V$, $V_{GE}=\pm 15V$, $R_g=2.7\Omega$




Switching loss vs. Gate resistance (typ.)
 $V_{CC}=600V$, $I_c=300A$, $V_{GE}=\pm 15V$, $T_j=125^\circ C$



Reverse bias safe operating area
 $+V_{GE}=15V$, $-V_{GE}\leq 15V$, $R_g\geq 2.7\Omega$, $T_j\leq 125^\circ C$




Forward current vs. Forward on voltage (typ.)




Reverse recovery characteristics (typ.)

$V_{CC} = 600\text{V}$, $V_{GE} = \pm 15\text{V}$, $R_g = 2.7\Omega$



Transient thermal resistance



Definitions of switching time

