

2MBI150N-120

IGBT Module

1200V / 150A 2 in one-package

■ Features

- High speed switching
- Voltage drive
- Low inductance module structure

■ Applications

- Inverter for Motor drive
- AC and DC Servo drive amplifier
- Uninterruptible power supply
- Industrial machines, such as Welding machines

■ Maximum ratings and characteristics

- Absolute maximum ratings (at $T_c=25^{\circ}\text{C}$ unless otherwise specified)


Item		Symbol	Rating	Unit
Collector-Emitter voltage		V _{CES}	1200	V
Gate-Emitter voltage		V _{GES}	±20	V
Collector current	Continuous	I _C	150	A
	1ms	I _C pulse	300	A
	Continuous	-I _C	150	A
	1ms	-I _C pulse	300	A
Max. power dissipation		P _C	1100	W
Operating temperature		T _J	+150	°C
Storage temperature		T _{stg}	-40 to +125	°C
Isolation voltage		V _{is}	AC 2500 (1min.)	V
Screw torque		Mounting *1	3.5	N·m
		Terminals *2	4.5	N·m

*1 : Recommendable value : 2.5 to 3.5 N·m(M5) or (M6)

*2 : Recommendable value : 3.5 to 4.5 N·m(M6)



■ Equivalent Circuit Schematic



- Electrical characteristics (at $T_j=25^{\circ}\text{C}$ unless otherwise specified)







Item	Symbol	Characteristics			Conditions	Unit
		Min.	Typ.	Max.		
Zero gate voltage collector current	I_{CES}	—	—	2.0	$V_{GE}=0\text{V}$, $V_{CE}=1200\text{V}$	mA
Gate-Emitter leakage current	I_{GES}	—	—	30	$V_{CE}=0\text{V}$, $V_{GE}=\pm 20\text{V}$	μA
Gate-Emitter threshold voltage	$V_{GE(th)}$	4.5	—	7.5	$V_{CE}=20\text{V}$, $I_c=150\text{mA}$	V
Collector-Emitter saturation voltage	$V_{CE(sat)}$	—	—	3.3	$V_{GE}=15\text{V}$, $I_c=150\text{A}$	V
Input capacitance	C_{ies}	—	24000	—	$V_{GE}=0\text{V}$	pF
Output capacitance	C_{oes}	—	8700	—	$V_{CE}=10\text{V}$	
Reverse transfer capacitance	C_{res}	—	7740	—	$f=1\text{MHz}$	
Turn-on time	t_{on}	—	0.65	1.2	$V_{CC}=600\text{V}$	μs
	t_r	—	0.25	0.6	$I_c=150\text{A}$	
Turn-off time	t_{off}	—	0.85	1.5	$V_{GE}=\pm 15\text{V}$	
	t_f	—	0.35	0.5	$R_G=5.6\text{ ohm}$	
Diode forward on voltage	V_F	—	—	3.0	$I_F=150\text{A}$, $V_{GE}=0\text{V}$	V
Reverse recovery time	t_{rr}	—	—	0.35	$I_F=150\text{A}$	μs

- Thermal resistance characteristics


Item	Symbol	Characteristics			Conditions	Unit
		Min.	Typ.	Max.		
Thermal resistance	$R_{th(j-c)}$	—	—	0.11	IGBT	$^{\circ}\text{C/W}$
	$R_{th(j-c)}$	—	—	0.33	Diode	$^{\circ}\text{C/W}$
	$R_{th(c-f)*3}$	—	0.025	—	the base to cooling fin	$^{\circ}\text{C/W}$

*3 : This is the value which is defined mounting on the additional cooling fin with thermal compound


■ Characteristics (Representative)




Switching time vs. R_G
 $V_{CC}=600V$, $I_C=150A$, $V_{GE}=\pm 15V$, $T_J=25^\circ C$




Dynamic input characteristics
 $T_J=25^\circ C$




Forward current vs. Forward voltage
 $V_{GE}=0V$




Reverse recovery characteristics
 t_{rr} , I_{rr} , vs. I_F





Switching loss vs. Collector current
 $V_{CC}=600V$, $R_G=5.6\text{ ohm}$, $V_{GE}=\pm 15V$




Reversed biased safe operating area
 $+V_{GE}=15V$, $-V_{GE} \leq 15V$, $T_J \leq 125^\circ C$, $R_G \geq 5.6\text{ ohm}$





■ Outline Drawings, mm



mass : 370g