

電 気 的 特 性 (Ta=25℃)													コンブリ メンタリ	外 形	備 考	型 名
Cis (typ) (pF)	Crs (typ) (pF)	VGS (V)	VDS (V)	NF typ dB	NF max dB	f (Hz)	Ro (Ω)	Rps(ON) (max) (Ω)	VGS (V)	Ip (A)	そ の 他 特 性	測 定 条 件				
2450	290	0	10					0.35	10	10	ton=145ns, toff=190nstyp	ID=10A, VDD=150V		253	GDS	2SK1497
2460	290	0	10					0.4	10	10	ton=145ns, toff=190nstyp	ID=10A, VDD=150V		253	GDS	2SK1498
3300	480	0	10					0.25	10	13	ton=180ns, toff=250nstyp	ID=13A, VDD=150V		253	GDS	2SK1499
3300	480	0	10					0.27	10	13	ton=180ns, toff=250nstyp	ID=13A, VDD=150V		253	GDS	2SK1500
790	55	0	10					4	10	2	ton=37ns, toff=105nstyp	ID=2A, VDD=150V	164/Z:306	GDS		2SK1501, 1501-Z
1550	75	0	10					2	10	4	ton=55ns, toff=190nstyp	ID=4A, VDD=150V		253	GDS	2SK1502
1200	70	0	25					0.9	10	5	ton=110ns, toff=240nstyp	ID=10A, VDD=300V		234	GDS	2SK1503
1750	400	0	25					0.022	10	17.5	ton=125ns, toff=480nstyp	ID=35A, VDD=12V		235	GDS	2SK1505
1800		0	10					0.75	10	8	ton=450ns, toff=100nstyp	ID=8A, VDD=300V		337	GDS	2SK1513
2500	200	0	10					0.03	10	20	ton=170ns, toff=620nstyp	ID=20A, VDD=30V		149	GDS	2SK1514
1100	50	0	10					0.8	10	5	ton=80ns, toff=150nstyp	ID=5A, VDD=30V		149	GDS	2SK1515
1100	50	0	10					0.9	10	5	ton=80ns, toff=150nstyp	ID=5A, VDD=30V		149	GDS	2SK1516
3050	140	0	10					0.25	10	10	ton=165ns, toff=345nstyp	ID=10A, VDD=30V		149	GDS	2SK1517
3050	140	0	10					0.27	10	10	ton=165ns, toff=345nstyp	ID=10A, VDD=30V		149	GDS	2SK1518
5800	170	0	10					0.15	10	15	ton=235ns, toff=615nstyp	ID=15A, VDD=30V		296	GDS	2SK1519
5800	170	0	10					0.16	10	15	ton=235ns, toff=615nstyp	ID=15A, VDD=30V		296	GDS	2SK1520
8700	235	0	10					0.1	10	25	ton=335ns, toff=850nstyp	ID=25A, VDD=30V		296	GDS	2SK1521
8700	235	0	10					0.11	10	25	ton=335ns, toff=850nstyp	ID=25A, VDD=30V		296	GDS	2SK1522
5800	150	0	10					0.15	10	20	ton=235ns, toff=580nstyp	ID=20A, VDD=30V		296		2SK1526
5800	150	0	10					0.16	10	20	ton=235ns, toff=580nstyp	ID=20A, VDD=30V		296		2SK1527
740	150	0	10					4	10	2	ton=75ns, toff=180nstyp	ID=2A, VDD=30V		294	GDS	2SK1528 (L) (S)
700	90	0	30								Coss=150pFtyp		2SJ200	184	GDS	2SK1529
900	100	0	30								Coss=180pFtyp		2SJ201	337	GDS	2SK1530
1480	240	0	10					0.45	10	7	ton=120ns, toff=250nstyp	ID=7A, VDD=210V		184	GDS	2SK1531
5.2	1.5	0	15											CMPAK		2SK1532
250	20							15			ton=40ns, toff=85nstyp			290	GDS	2SK1533
740	60							5			ton=45ns, toff=110nstyp			287		2SK1534
740	60							5			ton=45ns, toff=110nsty			288		2SK1535
740	60							5			ton=45ns, toff=110nstyp			289		2SK1536
1200	100							3			ton=65ns, toff=145nstyp			289		2SK1537