

Diode Module with Brake

Diode:1600V / 100A, IGBT:1400A/75A

■ Features

- Compact Package
- P.C. Board Mount Module
- Converter Diode Bridge Dynamic Brake Circuit

■ Applications

- Inverter for Motor Drive
- AC and DC Servo Drive Amplifier
- Uninterruptible Power Supply

■ Maximum ratings and characteristics

● Absolute maximum ratings (Tc=25°C unless without specified)

Item	Symbol	Condition		Rating	Unit
Converter	Repetitive peak reverse voltage	V _{RRM}		1600	V
	Non-repetitive peak reverse voltage	V _{RSM}		1760	V
	Average output current	I _o		100	A
	One cycle surge current	I _{FSM}		1000	A
	Peak current	I _p		4000	A ² s
	Operation junction temperature	T _j		-40 to +125	°C
Brake	Collector-Emitter voltage	V _{CES}		1400	V
	Gate-Emitter voltage	V _{GES}		±20	V
	Collector current	I _c	Tc=25°C	75	A
			Tc=75°C	50	
		I _{CP}	Tc=25°C	150	A
			Tc=75°C	100	
	Collector power dissipation	P _c		360	W
	Repetitive peak reverse voltage	V _{RRM}		1400	V
	Operation junction temperature	T _j		+150	°C
	Storage junction temperature	T _{stg}		-40 to +125	°C
Isolation voltage		V _{iso}		2500	V
Mounting screw torque				2.0 to 2.5	N·m


● Electrical characteristics (Tj=25°C unless otherwise specified)

Item	Symbol	Condition	Min.	Typ.	Max.	Unit
Co.	Forward voltage	Tj=25°C, I _{FM} =100A			1.30	V
	Reverse current	Tj=150°C, V _R =V _{RRM}			20	mA
	Zero gate voltage Collector current	V _{GE} =0V, V _{CE} =1400V			1.0	mA
	Gate-Emitter leakage current	V _{CE} =0V, V _{GE} =±20V			200	nA
	Collector-Emitter saturation voltage	V _{GE} =15V, I _c =50A		2.4	2.8	V
Brake	Turn-on time	V _{CC} =800V I _c =50A		0.35	1.2	μs
				0.25	0.6	
	Turn-off time	V _{GE} =±15V R _G =25ohm		0.45	1.0	
				0.08	0.3	
	Reverse current	I _{RRM}			1.0	mA


● Thermal characteristics

Item	Symbol	Condition		Min.	Typ.	Max.	Unit
Thermal resistance	R _{th(j-c)}	Converter	Per total loss			0.14	°C/W
			Per each device			0.84	
		Brake IGBT (1 device)				0.55	
Thermal Resistance(Case to fine)	R _{th(c-f)}	with thermal compound				0.08	°C/W


Forward Characteristics




Output Current - Total Loss




Output Current - Case Temperature




Surge Current









Transient Thermal Impedance




[Brake] Transient Thermal Impedance





■ Outline Drawings, mm



■ Equivalent Circuit Schematic

