

Vorläufige Daten
preliminary data**IGBT-Wechselrichter / IGBT-inverter****Höchstzulässige Werte / maximum rated values**

Kollektor-Emitter-Sperrspannung collector-emitter voltage	$T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = -25^{\circ}\text{C}$	V_{CES}	3300 3300	V
Kollektor-Dauergleichstrom DC-collector current	$T_C = 80^{\circ}\text{C}$ $T_C = 25^{\circ}\text{C}$	$I_{C\text{ nom}}$ I_C	800 1300	A A
Periodischer Kollektor Spitzenstrom repetitive peak collector current	$t_P = 1\text{ ms}$, $T_C = 80^{\circ}\text{C}$	I_{CRM}	1600	A
Gesamt-Verlustleistung total power dissipation	$T_C = 25^{\circ}\text{C}$	P_{tot}	9,60	kW
Gate-Emitter-Spitzenspannung gate-emitter peak voltage		V_{GES}	+/-20	V

Charakteristische Werte / characteristic values

			min.	typ.	max.	
Kollektor-Emitter Sättigungsspannung collector-emitter saturation voltage	$I_C = 800\text{ A}$, $V_{GE} = 15\text{ V}$, $T_{vj} = 25^{\circ}\text{C}$ $I_C = 800\text{ A}$, $V_{GE} = 15\text{ V}$, $T_{vj} = 125^{\circ}\text{C}$	$V_{CE\text{ sat}}$		3,40 4,30	4,25 5,00	V V
Gate-Schwellenspannung gate threshold voltage	$I_C = 80,0\text{ mA}$, $V_{CE} = V_{GE}$, $T_{vj} = 25^{\circ}\text{C}$	V_{GEth}	4,2	5,1	6,0	V
Gateladung gate charge	$V_{GE} = -15\text{ V} \dots +15\text{ V}$, $V_{CE} = 1800\text{ V}$	Q_G		15,0		μC
Interner Gatewiderstand internal gate resistor	$T_{vj} = 25^{\circ}\text{C}$	R_{Gint}		0,63		Ω
Eingangskapazität input capacitance	$f = 1\text{ MHz}$, $T_{vj} = 25^{\circ}\text{C}$, $V_{CE} = 25\text{ V}$, $V_{GE} = 0\text{ V}$	C_{ies}		100		nF
Rückwirkungskapazität reverse transfer capacitance	$f = 1\text{ MHz}$, $T_{vj} = 25^{\circ}\text{C}$, $V_{CE} = 25\text{ V}$, $V_{GE} = 0\text{ V}$	C_{res}		5,40		nF
Kollektor-Emitter Reststrom collector-emitter cut-off current	$V_{CE} = 3300\text{ V}$, $V_{GE} = 0\text{ V}$, $T_{vj} = 25^{\circ}\text{C}$	I_{CES}			5,0	mA
Gate-Emitter Reststrom gate-emitter leakage current	$V_{CE} = 0\text{ V}$, $V_{GE} = 20\text{ V}$, $T_{vj} = 25^{\circ}\text{C}$	I_{GES}			400	nA
Einschaltverzögerungszeit (ind. Last) turn-on delay time (inductive load)	$I_C = 800\text{ A}$, $V_{CE} = 1800\text{ V}$ $V_{GE} = \pm 15\text{ V}$, $R_{Gon} = 1,4\ \Omega$, $C_{GE} = 150\text{ nF}$, $T_{vj} = 25^{\circ}\text{C}$ $V_{GE} = \pm 15\text{ V}$, $R_{Gon} = 1,4\ \Omega$, $C_{GE} = 150\text{ nF}$, $T_{vj} = 125^{\circ}\text{C}$	$t_{d\text{ on}}$		0,28 0,28		μs μs
Anstiegszeit (induktive Last) rise time (inductive load)	$I_C = 800\text{ A}$, $V_{CE} = 1800\text{ V}$ $V_{GE} = \pm 15\text{ V}$, $R_{Gon} = 1,4\ \Omega$, $C_{GE} = 150\text{ nF}$, $T_{vj} = 25^{\circ}\text{C}$ $V_{GE} = \pm 15\text{ V}$, $R_{Gon} = 1,4\ \Omega$, $C_{GE} = 150\text{ nF}$, $T_{vj} = 125^{\circ}\text{C}$	t_r		0,18 0,20		μs μs
Abschaltverzögerungszeit (ind. Last) turn-off delay time (inductive load)	$I_C = 800\text{ A}$, $V_{CE} = 1800\text{ V}$ $V_{GE} = \pm 15\text{ V}$, $R_{Goff} = 1,8\ \Omega$, $C_{GE} = 150\text{ nF}$, $T_{vj} = 25^{\circ}\text{C}$ $V_{GE} = \pm 15\text{ V}$, $R_{Goff} = 1,8\ \Omega$, $C_{GE} = 150\text{ nF}$, $T_{vj} = 125^{\circ}\text{C}$	$t_{d\text{ off}}$		1,55 1,70		μs μs
Fallzeit (induktive Last) fall time (inductive load)	$I_C = 800\text{ A}$, $V_{CE} = 1800\text{ V}$ $V_{GE} = \pm 15\text{ V}$, $R_{Goff} = 1,8\ \Omega$, $C_{GE} = 150\text{ nF}$, $T_{vj} = 25^{\circ}\text{C}$ $V_{GE} = \pm 15\text{ V}$, $R_{Goff} = 1,8\ \Omega$, $C_{GE} = 150\text{ nF}$, $T_{vj} = 125^{\circ}\text{C}$	t_f		0,20 0,20		μs μs
Einschaltverlustenergie pro Puls turn-on energy loss per pulse	$I_C = 800\text{ A}$, $V_{CE} = 1800\text{ V}$, $L_S = 40\text{ nH}$ $V_{GE} = \pm 15\text{ V}$, $R_{Gon} = 1,4\ \Omega$, $C_{GE} = 150\text{ nF}$, $T_{vj} = 25^{\circ}\text{C}$ $V_{GE} = \pm 15\text{ V}$, $R_{Gon} = 1,4\ \Omega$, $C_{GE} = 150\text{ nF}$, $T_{vj} = 125^{\circ}\text{C}$	E_{on}		930 1450		mJ mJ
Abschaltverlustenergie pro Puls turn-off energy loss per pulse	$I_C = 800\text{ A}$, $V_{CE} = 1800\text{ V}$, $L_S = 40\text{ nH}$ $V_{GE} = \pm 15\text{ V}$, $R_{Goff} = 1,8\ \Omega$, $C_{GE} = 150\text{ nF}$, $T_{vj} = 25^{\circ}\text{C}$ $V_{GE} = \pm 15\text{ V}$, $R_{Goff} = 1,8\ \Omega$, $C_{GE} = 150\text{ nF}$, $T_{vj} = 125^{\circ}\text{C}$	E_{off}		870 1000		mJ mJ
Kurzschlußverhalten SC data	$t_P \leq 10\ \mu\text{s}$, $V_{GE} \leq 15\text{ V}$ $T_{vj} \leq 125^{\circ}\text{C}$, $V_{CC} = 2500\text{ V}$, $V_{CEmax} = V_{CES} - L_{sCE} \cdot di/dt$	I_{SC}		4000		A
Innerer Wärmewiderstand thermal resistance, junction to case	pro IGBT per IGBT	R_{thJC}			13,0	K/kW
Übergangs-Wärmewiderstand thermal resistance, case to heatsink	pro IGBT / per IGBT $\lambda_{Paste} = 1\text{ W/(m}\cdot\text{K)}$ / $\lambda_{grease} = 1\text{ W/(m}\cdot\text{K)}$	R_{thCH}		8,00		K/kW

prepared by: Jürgen Biermann

date of publication: 2003-6-13

approved by: Christoph Lübke

revision: 2.0

Vorläufige Daten
preliminary data

Diode-Wechselrichter / diode-inverter

Höchstzulässige Werte / maximum rated values

Periodische Spitzensperrspannung repetitive peak reverse voltage	$T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = -25^{\circ}\text{C}$	V_{RRM}	3300 3300	V
Dauergleichstrom DC forward current		I_F	800	A
Periodischer Spitzenstrom repetitive peak forward current	$t_P = 1 \text{ ms}$	I_{FRM}	1600	A
Grenzlastintegral I^2t - value	$V_R = 0 \text{ V}$, $t_P = 10 \text{ ms}$, $T_{vj} = 125^{\circ}\text{C}$	I^2t	220	kA^2s
Spitzenverlustleistung maximum power dissipation	$T_{vj} = 125^{\circ}\text{C}$	P_{RQM}	1600	kW
Mindesteinschaltzeit minimum turn-on time		$t_{Fon \text{ min}}$	10,0	μs

Charakteristische Werte / characteristic values

			min.	typ.	max.	
Durchlassspannung forward voltage	$I_F = 800 \text{ A}$, $V_{GE} = 0 \text{ V}$, $T_{vj} = 25^{\circ}\text{C}$ $I_F = 800 \text{ A}$, $V_{GE} = 0 \text{ V}$, $T_{vj} = 125^{\circ}\text{C}$	V_F		2,80 2,80	3,50 3,50	V V
Rückstromspitze peak reverse recovery current	$I_F = 800 \text{ A}$, $-di_F/dt = 4500 \text{ A}/\mu\text{s}$ $V_R = 1800 \text{ V}$, $V_{GE} = -15 \text{ V}$, $T_{vj} = 25^{\circ}\text{C}$ $V_R = 1800 \text{ V}$, $V_{GE} = -15 \text{ V}$, $T_{vj} = 125^{\circ}\text{C}$	I_{RM}		1100 1300		A A
Sperrverzögerungsladung recovered charge	$I_F = 800 \text{ A}$, $-di_F/dt = 4500 \text{ A}/\mu\text{s}$ $V_R = 1800 \text{ V}$, $V_{GE} = -15 \text{ V}$, $T_{vj} = 25^{\circ}\text{C}$ $V_R = 1800 \text{ V}$, $V_{GE} = -15 \text{ V}$, $T_{vj} = 125^{\circ}\text{C}$	Q_r		500 900		μC μC
Abschaltenergie pro Puls reverse recovery energy	$I_F = 800 \text{ A}$, $-di_F/dt = 4500 \text{ A}/\mu\text{s}$ $V_R = 1800 \text{ V}$, $V_{GE} = -15 \text{ V}$, $T_{vj} = 25^{\circ}\text{C}$ $V_R = 1800 \text{ V}$, $V_{GE} = -15 \text{ V}$, $T_{vj} = 125^{\circ}\text{C}$	E_{rec}		490 1150		mJ mJ
Innerer Wärmewiderstand thermal resistance, junction to case	pro Diode per diode	R_{thJC}			26,0	K/kW
Übergangs-Wärmewiderstand thermal resistance, case to heatsink	pro Diode / per diode $\lambda_{Paste} = 1 \text{ W}/(\text{m}\cdot\text{K})$ / $\lambda_{grease} = 1 \text{ W}/(\text{m}\cdot\text{K})$	R_{thCH}		16,0		K/kW

Technische Information / technical information

IGBT-Module
IGBT-modules

FD800R33KF2C-K

power electronics in motion
eupec

Vorläufige Daten preliminary data

Modul / module

Isolations-Prüfspannung insulation test voltage	RMS, f = 50 Hz, t = 1 min.	V _{ISOL}	6,0	kV
Teilentladungs Aussetzspannung partial discharge extinction voltage	RMS, f = 50 Hz, Q _{PD} ≤ 10 pC (acc. to IEC 1287)	V _{ISOL}	2,6	kV
Kollektor-Emitter-Gleichsperrspannung DC stability	T _{vj} = 25°C, 100 fit	V _{CE D}	1800	V
Material Modulgrundplatte material of module baseplate			AlSiC	
Material für innere Isolation material for internal insulation			AlN	
Kriechstrecke creepage distance	Kontakt - Kühlkörper / terminal to heatsink Kontakt - Kontakt / terminal to terminal		32,0 32,0	mm
Luftstrecke clearance distance	Kontakt - Kühlkörper / terminal to heatsink Kontakt - Kontakt / terminal to terminal		19,0 19,0	mm
Vergleichszahl der Kriechwegbildung comparative tracking index		CTI	> 400	
min. typ. max.				
Übergangs-Wärmewiderstand thermal resistance, case to heatsink	pro Modul / per module λ _{Paste} = 1 W/(m·K) / λ _{grease} = 1 W/(m·K)	R _{thCH}	4,00	K/kW
Modulinduktivität stray inductance module		L _{sCE}	12	nH
Modulleitungswiderstand, Anschlüsse - Chip module lead resistance, terminals - chip	T _C = 25°C, pro Zweig / per arm	R _{CC'+EE'} R _{AA'+CC'}	0,19 0,34	mΩ
Höchstzulässige Sperrschichttemperatur maximum junction temperature		T _{vj max}		150 °C
Temperatur im Schaltbetrieb temperature under switching conditions		T _{vj op}	-40	125 °C
Lagertemperatur storage temperature		T _{stg}	-40	125 °C
Anzugsdrehmoment f. mech. Befestigung mounting torque	Schraube / screw M6	M	4,25	- 5,75 Nm
Anzugsdrehmoment f. elektr. Anschlüsse terminal connection torque	Schraube / screw M4 Schraube / screw M8	M	1,8 8,0	- 2,1 10 Nm
Gewicht weight		G	1500	g

Modulinduktivität: IGBT (Zweig 1+2 parallel): 12nH; Diode (Zweig 3): 25nH
stray inductance module: IGBT (arm 1+2 parallel): 12nH; diode (arm 3): 25nH

Mit dieser technischen Information werden Halbleiterbauelemente spezifiziert, jedoch keine Eigenschaften zugesichert. Sie gilt in Verbindung mit den zugehörigen technischen Erläuterungen.


This technical information specifies semiconductor devices but guarantees no characteristics. It is valid with the appropriate technical explanations.

prepared by: Jürgen Biermann	date of publication: 2003-6-13
approved by: Christoph Lübke	revision: 2.0

Vorläufige Daten preliminary data


Ausgangskennlinie IGBT-Wechselr. (typisch)
output characteristic IGBT-inverter (typical)

$I_C = f(V_{CE})$
 $V_{GE} = 15 \text{ V}$




Ausgangskennlinienfeld IGBT-Wechselr. (typisch)
output characteristic IGBT-inverter (typical)

$I_C = f(V_{CE})$
 $T_{vj} = 125^\circ\text{C}$




Übertragungscharakteristik IGBT-Wechselr. (typisch)
transfer characteristic IGBT-inverter (typical)

$I_C = f(V_{GE})$
 $V_{CE} = 20 \text{ V}$



Schaltverluste IGBT-Wechselr. (typisch)
switching losses IGBT-inverter (typical)


$E_{on} = f(I_C)$, $E_{off} = f(I_C)$
 $V_{GE} = \pm 15 \text{ V}$, $R_{Gon} = 1,4 \Omega$, $R_{Goff} = 1,8 \Omega$, $V_{CE} = 1800 \text{ V}$,
 $T_{vj} = 125^\circ\text{C}$, $C_{GE} = 150 \text{ nF}$



Vorläufige Daten preliminary data


Schaltverluste IGBT-Wechselr. (typisch)
switching losses IGBT-Inverter (typical)

$E_{on} = f(R_G)$, $E_{off} = f(R_G)$
 $V_{GE} = \pm 15 \text{ V}$, $I_C = 800 \text{ A}$, $V_{CE} = 1800 \text{ V}$, $T_{vj} = 125^\circ\text{C}$,
 $C_{GE} = 150 \text{ nF}$




Transienter Wärmewiderstand IGBT-Wechselr.
transient thermal impedance IGBT-inverter

$Z_{thJC} = f(t)$




Sicherer Rückwärts-Arbeitsbereich IGBT-Wr. (RBSOA)
reverse bias safe operating area IGBT-inv. (RBSOA)

$I_C = f(V_{CE})$
 $V_{GE} = \pm 15 \text{ V}$, $R_{Goff} = 1,8 \Omega$, $T_{vj} = 125^\circ\text{C}$, $C_{GE} = 150 \text{ nF}$



Durchlaßkennlinie der Diode-Wechselr. (typisch)
forward characteristic of diode-inverter (typical)


$I_F = f(V_F)$




Vorläufige Daten
preliminary data

Schaltverluste Diode-Wechselr. (typisch)
switching losses diode-inverter (typical)


$$E_{rec} = f(I_F)$$

 $R_{Gon} = 1,4 \, \Omega$, $V_{CE} = 1800 \, V$, $T_{vj} = 125^\circ C$

Schaltverluste Diode-Wechselr. (typisch)
switching losses diode-inverter (typical)


$$E_{rec} = f(R_G)$$

 $I_F = 800 \, A$, $V_{CE} = 1800 \, V$, $T_{vj} = 125^\circ C$

Transienter Wärmewiderstand Diode-Wechselr.
transient thermal impedance diode-inverter

$$Z_{thJC} = f(t)$$


Sicherer Arbeitsbereich Diode-Wechselr. (SOA)
safe operation area diode-inverter (SOA)

$$I_R = f(V_R)$$

 $T_{vj} = 125^\circ C$


Terms & Conditions of Usage

Attention

The present product data is exclusively subscribed to technically experienced staff. This Data Sheet is describing the specification of the products for which a warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its specifications. Changes to the Data Sheet are reserved.

You and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application. Should you require product information in excess of the data given in the Data Sheet, please contact your local Sales Office via "www.eupec.com / sales & contact".

Warning

Due to technical requirements the products may contain dangerous substances. For information on the types in question please contact your local Sales Office via "www.eupec.com / sales & contact".