

型 名	社 名	f	最大定格 (Ta=25℃)				電 気 的 特 性 (Ta=25℃)																外 形 備 考		
			V _{DS} or V _{DG}	V _{GS}	I _D * /CH	P _D * /CH	I _{GSS}		I _{DSS}		V _{GS(th)}		V _{DS} = V _{GS}		R _{DS(on)}			I _{D(on)}		g _{fs}		C _{iss}		C _{oss}	C _{rss}
							(max)	V _{GS} (V)	(max)	V _{DS} (V)	min	max	I _D (mA)	*typ (Ω)	V _{GS} (V)	I _D (A)	(min) *typ (A)	V _{GS} (V)	(min) *typ (S)	I _D (A)	*typ (pF)	*typ (pF)		*typ (max) (pF)	
																									V _{GS} =0 V _{DS} (V)
IRFP9222	SAMSUNG	P	-200	±20	-3	40	±100	±20	-250	-200	-2	-4	-0.25	2.4	-10	-1.5	-3	-10	1	-1.5	400	125	45	-25	TO-3P
IRFP9223	SAMSUNG	P	-150	±20	-3	40	±100	±20	-250	-150	-2	-4	-0.25	2.4	-10	-1.5	-3	-10	1	-1.5	400	125	45	-25	TO-3P
IRFP9230	SAMSUNG	P	-200	±20	-6.5	75	±100	±20	-250	-200	-2	-4	-0.25	0.8	-10	-3.5	-6.5	-10	2.2	-3.5	650	300	90	-25	TO-3P
IRFP9231	SAMSUNG	P	-150	±20	-6.5	75	±100	±20	-250	-150	-2	-4	-0.25	0.8	-10	-3.5	-6.5	-10	2.2	-3.5	650	300	90	-25	TO-3P
IRFP9232	SAMSUNG	P	-200	±20	-5.5	75	±100	±20	-250	-200	-2	-4	-0.25	1.2	-10	-3.5	-5.5	-10	2.2	-3.5	650	300	90	-25	TO-3P
IRFP9233	SAMSUNG	P	-150	±20	-5.5	75	±100	±20	-250	-150	-2	-4	-0.25	1.2	-10	-3.5	-5.5	-10	2.2	-3.5	650	300	90	-25	TO-3P
IRFP9240	SAMSUNG	P	-200	±20	-12	150	±100	±20	-250	-200	-2	-4	-0.25	0.5	-10	-6	-11	-10	4	-6	1300	450	250	-25	TO-3P
IRFP9241	SAMSUNG	P	-150	±20	-12	150	±100	±20	-250	-150	-2	-4	-0.25	0.5	-10	-6	-11	-10	4	-6	1300	450	250	-25	TO-3P
IRFP9242	SAMSUNG	P	-200	±20	-10	150	±100	±20	-250	-200	-2	-4	-0.25	0.7	-10	-6	-9	-10	4	-6	1300	450	250	-25	TO-3P
IRFP9243	SAMSUNG	P	-150	±20	-10	150	±100	±20	-250	-150	-2	-4	-0.25	0.7	-10	-6	-9	-10	4	-6	1300	450	250	-25	TO-3P
IRFP9510	SAMSUNG	P	-100	±20	-3	20	±100	±20	-250	-100	-2	-4	-0.25	1.2	-10	-1.5	-3	-10	0.8	-1.5	250	100	35	-25	TO-220
IRFP9511	SAMSUNG	P	-60	±20	-3	20	±100	±20	-250	-60	-2	-4	-0.25	1.2	-10	-1.5	-3	-10	0.8	-1.5	250	100	35	-25	TO-220
IRFP9512	SAMSUNG	P	-100	±20	-2.5	20	±100	±20	-250	-100	-2	-4	-0.25	1.6	-10	-1.5	-2.5	-10	0.8	-1.5	250	100	35	-25	TO-220
IRFP9513	SAMSUNG	P	-60	±20	-2.5	20	±100	±20	-250	-60	-2	-4	-0.25	1.6	-10	-1.5	-2.5	-10	0.8	-1.5	250	100	35	-25	TO-220
IRFP9520	SAMSUNG	P	-100	±20	-6	40	±100	±20	-250	-100	-2	-4	-0.25	0.6	-10	-3	-6	-10	0.9	-3	450	350	100	-25	TO-220
IRFP9521	SAMSUNG	P	-60	±20	-6	40	±100	±20	-250	-60	-2	-4	-0.25	0.6	-10	-3	-6	-10	0.9	-3	450	350	100	-25	TO-220
IRFP9522	SAMSUNG	P	-100	±20	-5	40	±100	±20	-250	-100	-2	-4	-0.25	0.8	-10	-3	-5	-10	0.9	-3	450	350	100	-25	TO-220
IRFP9523	SAMSUNG	P	-60	±20	-5	40	±100	±20	-250	-60	-2	-4	-0.25	0.8	-10	-3	-5	-10	0.9	-3	450	350	100	-25	TO-220
IRFP9530	SAMSUNG	P	-100	±20	-12	75	±100	±20	-250	-100	-2	-4	-0.25	0.3	-10	-6.5	-12	-10	2	-6.5	700	450	200	-25	TO-220
IRFP9531	SAMSUNG	P	-60	±20	-12	75	±100	±20	-250	-60	-2	-4	-0.25	0.3	-10	-6.5	-12	-10	2	-6.5	700	450	200	-25	TO-220
IRFP9532	SAMSUNG	P	-100	±20	-10	75	±100	±20	-250	-100	-2	-4	-0.25	0.4	-10	-6.5	-10	-10	2	-6.5	700	450	200	-25	TO-220
IRFP9533	SAMSUNG	P	-60	±20	-10	75	±100	±20	-250	-60	-2	-4	-0.25	0.4	-10	-6.5	-10	-10	2	-6.5	700	450	200	-25	TO-220
IRFP9540	SAMSUNG	P	-100	±20	-19	125	±100	±20	-250	-100	-2	-4	-0.25	0.2	-10	-10	-19	-10	5	-10	1300	700	400	-25	TO-220
IRFP9541	SAMSUNG	P	-60	±20	-19	125	±100	±20	-250	-60	-2	-4	-0.25	0.2	-10	-10	-19	-10	5	-10	1300	700	400	-25	TO-220
IRFP9542	SAMSUNG	P	-100	±20	-15	125	±100	±20	-250	-100	-2	-4	-0.25	0.3	-10	-10	-15	-10	5	-10	1300	700	400	-25	TO-220
IRFP9543	SAMSUNG	P	-60	±20	-15	125	±100	±20	-250	-60	-2	-4	-0.25	0.3	-10	-10	-15	-10	5	-10	1300	700	400	-25	TO-220
IRFP9610	SAMSUNG	P	-200	±20	-1.75	20	±100	±20	-250	-200	-2	-4	-0.25	3	-10	-0.9	-1.75	-10	0.9	-0.9	300	100	35	-25	TO-220
IRFP9611	SAMSUNG	P	-150	±20	-1.75	20	±100	±20	-250	-150	-2	-4	-0.25	3	-10	-0.9	-1.75	-10	0.9	-0.9	300	100	35	-25	TO-220
IRFP9612	SAMSUNG	P	-200	±20	-1.5	20	±100	±20	-250	-200	-2	-4	-0.25	4.5	-10	-0.9	-1.5	-10	0.9	-0.9	300	100	35	-25	TO-220
IRFP9613	SAMSUNG	P	-150	±20	-1.5	20	±100	±20	-250	-150	-2	-4	-0.25	4.5	-10	-0.9	-1.5	-10	0.9	-0.9	300	100	35	-25	TO-220

チャネルの * は Pch と Nch の両方が入っていることを表す。