

International IOR Rectifier

SERIES IRK.136, .142, .162

**THYRISTOR/DIODE and
THYRISTOR/THYRISTOR**

NEW INT-A-pak Power Modules

135 A
140 A
160 A

Features

- High Voltage
- Electrically Isolated by DBC Ceramic (Al_2O_3)
- 3500 V_{RMS} Isolating Voltage
- Industrial Standard Package
- High Surge Capability
- Glass Passivated Chips
- Modules uses High Voltage Power thyristor/diodes in three Basic Configurations
- Simple Mounting
- UL E78996 approved 

Applications

- DC Motor Control and Drives
- Battery Charges
- Welders
- Power Converters
- Lighting Control
- Heat and Temperature Control

Major Ratings and Characteristics

Parameters	IRK.136..	IRK.142..	IRK.162..	Units
$I_{\text{T(AV)}}$	135	140	160	A
@ T_{C}	85	85	85	°C
$I_{\text{T(RMS)}}$	300	310	355	A
I_{TSM} @ 50Hz	3200	4500	4870	A
@ 60Hz	3360	4712	5100	A
I^2t @ 50Hz	51.5	102	119	KA^2s
@ 60Hz	47	92.5	108	KA^2s
$I^2\sqrt{t}$	515.5	1013	1190	$\text{KA}^2\sqrt{\text{s}}$
V_{RRM}	400 to 1600			V
T_{J} range	- 40 to 125			°C

CASE STYLE NEW INT-A-PAK



IRK.136, .142, .162 Series

Bulletin I27117 rev. B 03/00

International
IOR Rectifier**Electrical Specifications****Voltage Ratings**

Type number	Voltage Code	V_{RRM}/V_{DRM} , Maximum repetitive peak reverse voltage V	V_{RSM}/V_{DSM} , Maximum non-repetitive peak reverse voltage V	I_{RRM}/I_{DRM} @ 125°C mA
IRK.136	04	400	500	50
IRK.142	08	800	900	
IRK.162	12	1200	1300	
	14	1400	1500	
	16	1600	1700	

Forward Conduction

Parameter	IRK.136	IRK.142	IRK.162	Units	Conditions			
$I_{T(AV)}$ Max. average on-state current @ Case temperature	135	140	160	A	180° conduction, half sine wave			
	85	85	85	°C				
$I_{T(RMS)}$ Max. RMS on-state current	300	310	355	A	as AC switch			
I_{TSM} Maximum peak, one-cycle on-state, non-repetitive surge current	3200	4500	4870	A	t = 10ms	No voltage	Sine half wave, Initial $T_J = T_J$ max.	
	3360	4712	5100		t = 8.3ms	reapplied		
	2700	3785	4100		t = 10ms	100% V_{RRM}		
	2800	3963	4300		t = 8.3ms	reapplied		
I^2t Maximum I^2t for fusing	51.5	102	119	KA ² s	t = 10ms	No voltage		
	47	92.5	108		t = 8.3ms	reapplied		
	36.5	71.6	84		t = 10ms	100% V_{RRM}		
	33.3	65.4	76.7		t = 8.3ms	reapplied		
$I^2\sqrt{t}$ Maximum $I^2\sqrt{t}$ for fusing	515.5	1013	1190	KA ² √s	t = 0.1 to 10ms, no voltage reapplied			
$V_{T(TO)1}$ Low level value of threshold voltage	0.86	0.83	0.8	V	(16.7% $\times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)}$), @ T_J max.			
$V_{T(TO)2}$ High level value of threshold voltage	1.05	1	0.98		(I $> \pi \times I_{T(AV)}$), @ T_J max.			
r_{t1} Low level value on-state slope resistance	2.02	1.78	1.67	mΩ	(16.7% $\times \pi \times I_{T(AV)} < I < \pi \times I_{T(AV)}$), @ T_J max.			
r_{t2} High level value on-state slope resistance	1.65	1.43	1.38		(I $> \pi \times I_{T(AV)}$), @ T_J max.			
V_{TM} Maximum forward voltage drop	1.57	1.55	1.54	V	$I_{TM} = \pi \times I_{T(AV)}$, $T_J = 25^\circ\text{C}$, 180°conduction			
I_H Maximum holding current	200			mA	Anode supply = 6V initial $I_T = 30\text{A}$, $T_J = 25^\circ\text{C}$			
I_L Maximum latching current	400			mA	Anode supply = 6V resistive load = 1Ω Gate pulse: 10V, 100μs, $T_J = 25^\circ\text{C}$			

Switching

t_{gd} Typical delay time	1	μs	$T_J = 25^\circ\text{C}$	Gate Current=1A $di/dt=1\text{A}/\mu\text{s}$ $V_d=0,67\% V_{DRM}$
t_{gr} Typical rise time	2		$T_J = 25^\circ\text{C}$	
t_q Typical turn-off time	50 - 200		$I_{TM} = 300\text{A}$; $-di/dt = 15\text{A}/\mu\text{s}$; $T_J = T_J \text{ max}$ $V_r = 50\text{V}$; $dV/dt = 20\text{V}/\mu\text{s}$; Gate 0 V, 100Ω	

Blocking

I_{RRM}	Maximum peak reverse and off-state leakage current	50	mA	$T_J = 125^\circ\text{C}$
V_{INS}	RMS isolation voltage	3500	V	50Hz, circuit to base, all terminals shorted, $t = 1\text{s}$
dV/dt	critical rate of rise of off-state voltage	1000	V/ μs	$T_J = T_{J\text{ max.}}$, exponential to 67% rated V_{DRM}

Triggering

Parameter		IRK.136	IRK.142	IRK.162	Units	Conditions	
P _{GM}	Max. peak gate power	12			W	tp≤5ms, T _J = T _J max.	
P _{G(AV)}	Max. average gate power	3			W	f=50Hz, T _J = T _J max.	
I _{GM}	Max. peak gate current	3			A	tp≤5ms, T _J = T _J max.	
-V _{GT}	Max. peak negative gate voltage	10			V		
V _{GT}	Max. required DC gate voltage to trigger	4			V	T _J = - 40°C	Anode supply = 6V, resistive load; Ra = 1Ω
		2.5				T _J = 25°C	
		1.7				T _J = T _J max.	
I _{GT}	Max. required DC gate current to trigger	270			mA	T _J = - 40°C	Anode supply = 6V, resistive load; Ra = 1Ω
		150				T _J = 25°C	
		80				T _J = T _J max.	
V _{GD}	Max. gate voltage that will not trigger	0.3			V	@ T _J = T _J max., rated V _{DRM} applied	
I _{GD}	Max. gate current that will not trigger	10			mA		
di/dt	Max. rate of rise of turned-on current	300			A/μs	@ T _J = T _J max., I _{TM} = 400A rated V _{DRM} applied	

Thermal and Mechanical Specifications

Parameter		IRK.136	IRK.142	IRK.162	Units	Conditions
T _J	Max. junction operating temperature range	-40 to 125			°C	
T _{stg}	Max. storage temperature range	-40 to 150			°C	
R _{thJC}	Max. thermal resistance, junction to case	0.18	0.18	0.16	K/W	DC operation, per junction
R _{thCS}	Max. thermal resistance, case to heatsink	0.05			K/W	Mounting surface smooth, flat and greased Per module
T	Mounting IAP to heatsink	4 to 6			Nm	A mounting compound is recommended and the torque should be rechecked after a period of 3 hours to allow for the spread of the compound. Lubricated threads.
	torque ± 10% busbar to IAP	4 to 6				
wt	Approximate weight	200 (7.1)			g(oz)	
Case Style		New Int-A-Pak				

ΔR Conduction (per Junction)

(The following table shows the increment of thermal resistance R_{thJC} when devices operate at different conduction angles than DC)

Devices	Sinusoidal conduction @ $T_J\text{ max.}$					Rectangular conduction @ $T_J\text{ max.}$					Units
	180°	120°	90°	60°	30°	180°	120°	90°	60°	30°	
IRK.136	0.007	0.01	0.013	0.0155	0.017	0.009	0.012	0.014	0.015	0.017	K/W
IRK.142	0.0019	0.0019	0.0020	0.0020	0.0021	0.0018	0.0022	0.0023	0.0023	0.0020	
IRK.162	0.0030	0.0031	0.0032	0.0033	0.0034	0.0029	0.0036	0.0039	0.0041	0.0040	

IRK.136, .142, .162 Series


Bulletin I27117 rev. B 03/ 00

Ordering Information Table

Device Code				
IRK	T	162	/	16
1	2	3		4
1	-			
2	-			
3	-			
4	-			

1 - Module Type
2 - Circuit Configuration
3 - Current Rating: $I_{T(AV)}$
4 - Voltage Code: Code x 100 = V_{RRM}






Outline Table



IRKT

IRKH

IRKL



NOTE: To order the Optional Hardware see Bulletin I27900




Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 3 - On-State Power Loss Characteristics




Fig. 4 - On-State Power Loss Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig.7 - On State Power Loss Characteristics




Fig.8 - On State Power Loss Characteristics




Fig.9 - On State Power Loss Characteristics




Fig. 10 - Current Ratings Characteristics




Fig. 11 - Current Ratings Characteristics




Fig. 12 - On-State Power Loss Characteristics




Fig. 13 - On-State Power Loss Characteristics




Fig. 14 - Maximum Non-Repetitive Surge Current




Fig. 15 - Maximum Non-Repetitive Surge Current




Fig.16 - On State Power Loss Characteristics




Fig.17 - On State Power Loss Characteristics




Fig.18 - On State Power Loss Characteristics




Fig. 19 - Current Ratings Characteristics




Fig. 20 - Current Ratings Characteristics




Fig. 21 - On-State Power Loss Characteristics




Fig. 22 - On-State Power Loss Characteristics




Fig. 23 - Maximum Non-Repetitive Surge Current




Fig. 24 - Maximum Non-Repetitive Surge Current




Fig.25 - On State Power Loss Characteristics




Fig.26 - On State Power Loss Characteristics




Fig.27 - On State Power Loss Characteristics




Fig.28 - On State Voltage Drop Characteristics




Fig.29 - On State Voltage Drop Characteristics




Fig.30 - On State Voltage Drop Characteristics




Fig.31 - Thermal Impedance Z_{thJC} Characteristics




Fig.32 - Thermal Impedance Z_{thJC} Characteristics




Fig.33 - Thermal Impedance Z_{thJC} Characteristics




Fig. 34 - Gate Characteristics