

型 番	社 名	最 大 定 格								動 作 特 性										備 考
		1 次 側		2 次 側		全 体		1 次 側		2 次 側		1 次 - 2 次 間								
		I_F max (mA)	V_R max (V)	P_{D1} max (mW)	V_{CE} max (V) V_{CC}^*	I_{OL} max (mA)	P_{D2} max (mW)	BV min (kV) DC/AC*	T_a min (°C)	V_F max / I_F (V/mA)	C_i max typ* (pF)	t_r max typ* (μs)	t_f max typ* (μs)	h_{FE} min typ*	CTR min / I_F (%/mA)	V_{CES} max / I_F, I_C (V/mA, mA)	C_{1-2} max typ* (pF)	t_{pd} max typ* (μs)	f_T min typ* (MHz)	
PS2801-4	日 電	50	6	80	80	50	120	2.5*	-55~100	1.4/10	30*	3*	5*	—	80/5	0.3/10,2	0.4*	—	—	4 回路, 小型 SOP
形EE-CF1/2/4	オムロン	50	4	—	30	30	150	5*	-30~90	1.5/30	—	3*	3*	—	50/10	0.4/20,2	1*	—	—	1/2/4は1,2,4 回路
OC360	沖	50	3	75	30	—	100	2.5*	-20~100	1.6/50	—	4*	4*	—	30/5	0.4/16,2	1.3*	—	—	2 回路
PC120/120F	シャープ	50	6	70	35	50	150	5*	-30~100	1.4/20	250	18	18	—	50/5	0.2/20,1	1.0	—	—	1 回路
PC121/121F	"	"	"	"	70	"	"	"	"	"	"	"	"	—	"	"	"	—	—	-Fは400ミル幅
PC810	シャープ	50	6	70	35	50	150	5*	-30~100	1.4/20	200	50	50	—	60/1	0.2/20,1	1.0	—	—	1 回路
PC812	"	"	"	"	"	"	"	"	"	"	"	18	20	—	90/5	"	"	—	—	1 回路
PC816/826/846	シャープ	50	6	70	70	50	150	5*	-30~100	1.4/20	250	18	18	—	50/5	0.2/20,1	1.0	—	—	1/2/4 回路
PC817/827/837/847	シャープ	50	6	70	35	50	150	5*	-30~100	1.4/20	250	18	18	—	50/5	0.2/20,1	1.0	—	—	1/2/3/4 回路
PC818	シャープ	50	6	70	35	50	150	5*	-30~100	1.4/20	250	40	40	—	10/1	0.4/20,5	1.0	—	—	1 回路
PC851	シャープ	50	6	70	300	50	150	5*	-25~100	1.4/20	250	10	12	—	40/5	0.3/20,1	1.0	—	—	1 回路、2次側高耐圧
PC866/8D66/8Q66	シャープ	50	6	70	80	50	150	5*	-30~100	1.4/20	250	8*	8*	—	100/1	0.4/1,0.2	1.0	—	—	1/2/4 回路
PS2561-1	日 電	80	6	150	80	50	150	5*	-55~100	1.4/10	50*	3*	5*	—	80/5	0.3/10,2	0.5*	—	—	1/2 回路
PS2561-2	"	"	"	120	"	"	120	—	"	"	"	"	"	—	"	"	"	—	—	
PC316/3D16/3Q16	シャープ	50	6	70	120	50	150	2.5*	-30~100	1.4/20	250	18	18	—	50/5	0.2/20,1	1.0	—	—	1/2/4 回路
PC356T	"	"	"	"	80	"	"	3.75*	"	"	"	6*	8*	—	100/1	"	"	—	—	1 回路
PC317/3D17/3Q17	"	"	"	"	35	"	"	2.5*	"	"	"	18	18	—	50/5	"	"	—	—	1/2/4 回路
PC357T	"	"	"	"	"	"	"	3.75*	"	"	"	"	"	—	"	"	"	—	—	1 回路
PC358T	"	"	"	"	120	"	"	"	"	"	"	"	"	—	"	"	"	—	—	1 回路

ミニ
フラット