


Powerex, Inc., Hillis Street, Youngwood, Pennsylvania 15697 (724) 925-7272

POW-R-BLOK™ Dual Diode Isolated Module 1000 Amperes / Up to 4400 Volts



Description:

Powerex Dual Diode Modules are designed for use in applications requiring rectification and isolated packaging. The modules are isolated for easy mounting with other components on a common heatsink.

Features:

- Electrically Isolated Heatsinking
- Compression Bonded Elements
- Metal Baseplate
- Low Thermal Impedance for Improved Current Capability

Benefits:

- No Additional Insulation Components Required
- Easy Installation
- No Clamping Components Required
- Reduce Engineering Time

Applications:

- Bridge Circuits
- AC & DC Motor Drives
- Battery Supplies
- Power Supplies
- Large IGBT Circuit Front Ends

Ordering Information:

Select the complete eight-digit module part number from the table below.

Example: PD414410 is a 4400 Volt, 1000A Average Dual Diode Isolated POW-R-BLOK™ Module

Type	Voltage Volts (x100)	Current Amperes (x100)
PD41	36	10
	38	
	40	
	42	
	44	

Powerex, Inc., Hillis Street, Youngwood, Pennsylvania 15697 (724) 925-7272

POW-R-BLOK™
Dual Diode Isolated Module
1000 Amperes / Up to 4400 Volts

Absolute Maximum Ratings

Characteristics	Conditions	Symbol	Units
Repetitive Peak Reverse Blocking Voltage		V_{RRM}	Up to 4400 V
Non-Repetitive Peak Blocking Voltage ($t < 5$ msec)		V_{RSM}	$V_{RRM} + 100V$ V
RMS Current Per Diode (180° Conduction)	180° Conduction, $T_C=79^{\circ}C$	$I_{F(RMS)}$	1725 A
	180° Conduction, $T_C=87^{\circ}C$	$I_{F(RMS)}$	1570 A
	180° Conduction, $T_C=95^{\circ}C$	$I_{F(RMS)}$	1415 A
	180° Conduction, $T_C=103^{\circ}C$	$I_{F(RMS)}$	1255 A
Average Forward Current Per Diode (180° Conduction)	180° Conduction, $T_C=79^{\circ}C$	$I_{F(AV)}$	1100 A
	180° Conduction, $T_C=87^{\circ}C$	$I_{F(AV)}$	1000 A
	180° Conduction, $T_C=95^{\circ}C$	$I_{F(AV)}$	900 A
	180° Conduction, $T_C=103^{\circ}C$	$I_{F(AV)}$	800 A
Peak One Cycle Surge Current, Non-Repetitive $T_J = 25C, V_r = 0$	60 Hz	I_{FSM}	48,300 A
	50 Hz	I_{FSM}	41,060 A
Peak One Cycle Surge Current, Non-Repetitive $T_J = 25C, V_r = V_{rrm}$	60 Hz	I_{FSM}	32,200 A
	50 Hz	I_{FSM}	27,375 A
Peak One Cycle Surge Current, Non-Repetitive $T_J = 125C, V_r = 0$	60 Hz	I_{FSM}	42,000 A
	50 Hz	I_{FSM}	35,700 A
Peak One Cycle Surge Current, Non-Repetitive $T_J = 125C, V_r = V_{rrm}$	60 Hz	I_{FSM}	28,000 A
	50 Hz	I_{FSM}	23,800 A
Peak Three Cycle Surge Current, Non-Repetitive	60 Hz, $T_J = 125C, V_r = V_{rrm}$	I_{FSM}	22,480 A
Peak Ten Cycle Surge Current, Non-Repetitive	60 Hz, $T_J = 125C, V_r = V_{rrm}$	I_{FSM}	17,660 A
I^2t for Fusing for One Cycle $T_J = 125C, V_r = V_{rrm}$	8.3 milliseconds	I^2t	3.26×10^6 A ² sec
	10 milliseconds	I^2t	2.83×10^6 A ² sec
I^2t for Fusing for One Cycle $T_J = 25C, V_r = 0$	8.3 milliseconds	I^2t	9.72×10^6 A ² sec
	10 milliseconds	I^2t	8.43×10^6 A ² sec
Operating Temperature		T_J	-40 to +150 °C
Storage Temperature		T_{stg}	-40 to +150 °C
Max. Mounting Torque, M6 Mounting Screw			132 in. – Lb. 15 Nm
Max. Mounting Torque, M10 Terminal Screw			106 in. – Lb. 12 Nm
Module Weight, Typical			455 g 11.75 lb
V Isolation @ 25C	60Hz V_{rms} 60 sec	V_{rms}	3600 V

Powerex, Inc., Hillis Street, Youngwood, Pennsylvania 15697 (724) 925-7272

POW-R-BLOK™
Dual Diode Isolated Module
1000 Amperes / Up to 4400 Volts

Electrical Characteristics, T_J=25°C unless otherwise specified

Characteristics	Symbol	Test Conditions	Min.	Max.	Units
Repetitive Peak Reverse Leakage Current	I _{RRM}	Up to 4400V, T _J =125°C		200	mA
Peak On-State Voltage	V _{FM}	I _{FM} =3000A, T _J =25°C		1.35	V
Threshold Voltage, Low-level	V _{(TO)1}	T _J = 125°C, I = 15%I _{T(AV)} to π I _{T(AV)}		0.741	V
Slope Resistance, Low-level	r _{T1}			0.132	mΩ
Threshold Voltage, High-level	V _{(TO)2}	T _J = 125°C, I = π I _{T(AV)} to I _{TSM}		0.840	V
Slope Resistance, High-level	r _{T2}			0.1194	mΩ
V _{FM} Coefficients, Full Range		T _J = 125°C, I = 50A to 6kA V _{FM} = A+ B Ln I +C I + D Sqrt I	A = B = C = D =	0.7903 -1.11 E-02 1.27 E-04 1.00 E-03	
Typical Reverse Recovery Time	t _{rr}	T _J = 25°C, I _f m = 1500A. di _r /dt = 25 A/us, t _p = 190 us		25	us


Thermal Characteristics

Characteristics	Symbol		Max.	Units
Thermal Resistance, Junction to Case	R _{ΘJ-C}	Per Module, both conducting Per Junction, both conducting	0.029 0.058	°C/W °C/W
Thermal Impedance Coefficients	Z _{ΘJ-C}	Z _{ΘJ-C} = K ₁ (1-exp(-t/t ₁)) + K ₂ (1-exp(-t/t ₂)) + K ₃ (1-exp(-t/t ₃)) + K ₄ (1-exp(-t/t ₄))	K ₁ = 5.04 E-04 K ₂ = 2.31 E-03 K ₃ = 2.83 E-03 K ₄ =5.24 E-02	t ₁ = 2.47 E-03 t ₂ = 4.42 E-02 t ₃ = 1.370 t ₄ = 9.668
Thermal Resistance, Case to Sink Lubricated	R _{ΘC-S}	Per Module	0.009	°C/W


Powerex, Inc., Hillis Street, Youngwood, Pennsylvania 15697 (724) 925-7272

Dual Diode Module 1000 Amperes / Up to 4400 Volts


Typical On-State Forward Voltage Drop
($T_J = 150^\circ\text{C}$)




Maximum Transient Thermal Impedance
(Junction To Case)




Maximum On-State Power Dissipation
(Sinusoidal Waveform)




Maximum Allowable Case Temperature
(Sinusoidal Waveform)



Maximum On-State Power Dissipation
(Rectangular Waveform)



Maximum Allowable Case Temperature
(Rectangular Waveform)



Powerex, Inc., Hillis Street, Youngwood, Pennsylvania 15697 (724) 925-7272

Dual Diode Module

1000 Amperes / Up to 4400 Volts

DIM.		INCHES		MILLIMETERS	
A	7.80		198.1		
B	4.00		101.6		
C	2.68		68.1		
D	6.44		163.6		
E	3.44		87.4		
F	.28		7.1		
G	7.31		185.7		
H	7.00		177.8		
M	.281		7.1		
N	.45		11.4		
P	.54		13.7		
Q	5.93		150.6		
R	.19		4.8		
T	.48		12.2		
U	2.28		58		
W	4.93		125.2		
X	3.81		96.8		
Z	2.00		50.8		
AA	1.00		25.4		
BB	.50		12.7		
CC	1.00		25.4		
DD	.406		10.3		
EE	2.87		72.9		
FF	.66		16.8		

