

THYRISTOR MODULE

P D T 1 5 1 8 P D H 1 5 1 8

150A / 800V

OUTLINE DRAWING


FEATURES

- * 108mm Short Size Case
- * Isolated Base
- * Dual Thyristors or Thyristor and Diode Cascaded Circuit
- * High Surge Capability
- * UL Recognized, File No. E187184



TYPICAL APPLICATIONS

- * Rectified For General Use

PDT



PDH



Maximum Ratings

Approx Net Weight:280g

Parameter	Symbol	Grade	Unit
		PDT/PDH1518	
Repetitive Peak Off-State Voltage	V_{DRM}	800	V
Non Repetitive Peak Off-State Voltage	V_{DSM}	900	
Repetitive Peak Reverse Voltage	V_{RRM}	800	V
Non Repetitive Peak Reverse Voltage	V_{RSM}	900	

Parameter		Conditions	Max Rated Value	Unit
Average Rectified Output Current	$I_{O(AV)}$	50Hz Half Sine Wave condition $T_c=78^{\circ}C$	150	A
RMS On-State Current	$I_{T(RMS)}$		235	A
Surge On-State Current	I_{TSM}	50 Hz Half Sine Wave,1Pulse Non-Repetitive	3200	A
I Squared t	I^2t	2msec to 10msec	51200	A ² s
Critical Rate of Turned-On Current	di/dt	$V_D=2/3V_{DRM}$, $I_{TM}=2 \cdot I_O$, $T_j=125^{\circ}C$ $I_G=300mA$, $di_G/dt=0.2A/\mu s$	100	A/ μs
Peak Gate Power	P_{GM}		5	W
Average Gate Power	$P_{G(AV)}$		1	W
Peak Gate Current	I_{GM}		2	A
Peak Gate Voltage	V_{GM}		10	V
Peak Gate Reverse Voltage	V_{RGM}		5	V
Operating JunctionTemperature Range	T_{jw}		-40 to +125	$^{\circ}C$
Storage Temperature Range	T_{stg}		-40 to +125	$^{\circ}C$
Isoration Voltage	Viso	Base Plate to Terminals, AC1min	2500	V
Mounting torque	Case mounting	Ftor	M6 Screw	N.m
	Terminals		M6 Screw	



Value per 1 Arm

Electrical • Thermal Characteristics

Characteristics	Symbol	Test Conditions	Maximum Value.			Unit
			Min.	Typ.	Max.	
Peak Off-State Current	I_{DM}	$V_{DM} = V_{DRM}, T_j = 125^{\circ}\text{C}$			15	mA
Peak Reverse Current	I_{RM}	$V_{RM} = V_{RRM}, T_j = 125^{\circ}\text{C}$			15	mA
Peak Forward Voltage	V_{TM}	$I_{TM} = 450\text{A}, T_j = 25^{\circ}\text{C}$			1.36	V
Gate Current to Trigger	I_{GT}	$V_D = 6\text{V}, I_T = 1\text{A}$	$T_j = -40^{\circ}\text{C}$		300	mA
			$T_j = 25^{\circ}\text{C}$		150	
			$T_j = 125^{\circ}\text{C}$		80	
Gate Voltage to Trigger	V_{GT}	$V_D = 6\text{V}, I_T = 1\text{A}$	$T_j = -40^{\circ}\text{C}$		5	V
			$T_j = 25^{\circ}\text{C}$		3	
			$T_j = 125^{\circ}\text{C}$		2	
Gate Non-Trigger Voltage	V_{GD}	$V_D = 2/3 V_{DRM}, T_j = 125^{\circ}\text{C}$	0.25			V
Critical Rate of Rise of Off-State Voltage	dv/dt	$V_D = 2/3 V_{DRM}, T_j = 125^{\circ}\text{C}$	500			V/ μs
Turn-Off Time	t_q	$I_{TM} = I_O, V_D = 2/3 V_{DRM}$ $dv/dt = 20\text{V}/\mu\text{s}, V_R = 100\text{V}$ $-di/dt = 20\text{A}/\mu\text{s}, T_j = 125^{\circ}\text{C}$		100		μs
Turn-On Time	t_{gt}	$V_D = 2/3 V_{DRM}, T_j = 125^{\circ}\text{C}$ $I_G = 300\text{mA}, di_G/dt = 0.2\text{A}/\mu\text{s}$		6		μs
Delay Time	t_d			2		μs
Rise Time	t_r			4		μs
Latching Current	I_L	$T_j = 25^{\circ}\text{C}$		100		mA
Holding Current	I_H	$T_j = 25^{\circ}\text{C}$		60		
Thermal Resistance	$R_{th(j-c)}$	Junction to Case			0.25	$^{\circ}\text{C}/\text{W}$
	$R_{th(c-f)}$	Base Plate to Heat Sink with Thermal Compound			0.1	


Value Per 1Arm

PDT/PDH1518 OUTLINE DRAWING (Dimensions in mm)



ON-STATE CURRENT VS. VOLTAGE



PDT/PDH1518




AVERAGE ON-STATE POWER DISSIPATION


for

PDT/PDH1518




AVERAGE ON-STATE CURRENT VS. CASE TEMPERATURE







AVERAGE ON-STATE CURRENT VS. CASE TEMPERATURE



GATE CHARACTERISTICS




GATE RATINGS



SURGE CURRENT RATINGS

f=50Hz,Harf Sine Wave,Non-Repetitive,On Load

PDT/PDH1518



MAXIMUM TRANSIENT THERMAL IMPEDANCE

Junction to Case

PDT/PDH1518

